SPECIFICATIONS

ITEM NO.	DESCRIPTION	CHECK ✓ IF AS SPECIFIED	DESCRIBE FULLY IF NOT AS SPECIFIED
1.	**14' Dry cargo box installed on chassis with lift gate. All specifications as listed below**		
	Vendor to pick up both vehicles from Coyote Ridge Corrections Center and deliver completed vehicle with box and lift installed.		
	Height 84" to 96"		
	96" Width		
	040 Aluminum pre-painted white side sheets		
	Z-shaped side posts on 16" centers		
	3/16" solid buck rivets spaced 4" apart on center panels		
	3/16" Solid buck rivets on 2" centers on end panel seams		
	Extruded aluminum top and bottom rails		
	5" Radius extruded aluminum front corner posts		
	All steel rear frame		
	12" Aerodynamic radius front		
	Smooth aluminum radius corners		
	3" structural cross-members on 16" centers		
	.032 aluminum one piece roof sheet		
	Galvanized anti-snag roof bows		
	Complete body undercoated		
	Two (2) grab handles		
	Flush to floor rear entry		
	Dome Light with Switch at Right Rear Inside Door		
	1-1/8" hardwood floor		
	Tread plate radius		
	3/8" Plywood Lining- full height		
	1/2" Plywood Full Height on Front		

	E-Track, One row per side for securing cargo		
	Full Width Roll Up Rear Door includes 2" nylon rollers		
	ICC Drop Bumper		
	Cross Sills @ 12"		
	4" structural longitudinal body sills grade 80 steel		
	Mirror – 12" cross view mirror mounted on left rear corner of box		
	All lights and reflectors meet FMVSS 108 requirements, and		
	Mud flaps installed.		
	Mounting on Ford F-550 Reg Cab 189WB 108CA 4 x 2 DRW Cab Chassis-19,500 GVWR		
2.	**Lift Gate, Maxon, Raillift, Model RC-3 or equal**		
	3000 lb capacity		
	Rail Lift System		
	Travel 44" min 56" max		
	Folding 66" x 90" platform		
	Low profile		
	Single cylinder operation		
	Roller bearings on both ends of runners		
	Lifetime guaranteed side chain on platform		
	Emergency Cable Brake		
	Platform reinforced with welded 4" support tubes		
	Sliding block platform locks		
	Single switch operation		
	Installed on each of the boxes listed in item (1)		